



	Serial Hub 8-Port (99465-7)	Serial Hub 16-Port (99460-2)	PRO 8-Port (99443-5)	PRO 16-Port (99451-0)	FreeWire (31300-7)
Hardware					
Number of ports: 10/100Base-TX	2	1	2	2	1 x 10/10Base-Tx 1 x 802.11b/g
Number of Serial ports	8 x RS232	16 x RS232	8 x RS232/422/485	16 x RS232/422/485	1 x RS232
Serial Baud Rate	300 to 230.4Kbps	300 to 230.4Kbps	300 to 230.4Kbps	300 to 230.4Kbps	300 to 921Kbps
Serial Interface	DB9M	DB9M	RJ45	RJ45	DB9M
Power Input	9-30VDC Terminal External Power Supply included: 90- 240VAC (US/EU) input	100-240VAC (US/EU Cord)	9-30VDC Terminal External Power Supply included: 90- 240VAC (US/EU) input	100-240VAC (US/EU Cord)	4.75 - 5.25 VDC *External Power Supply included: 5VDC
Serial Surge protect	15KV	15KV	25KV	25KV	15KV
Environmental Specifications					
MTBF	24 Years	9.5 Years	18.2 Years	7.3 Years	
Enclosure	Black Finished Steel	Black Finished Steel	Black Finished Steel	Black Finished Steel	Metal IP40 rating
Dimension	19.63" x 4" x 14"	17.25" x 1.75" x 11"	10.8" x 1.8" x 6.3"	17.25" x 1.74" x 8.0"	4.95" x 0.95" x 2.96"
Operating temperature	-37°~ 74°C	-37°~ 74°C	-37°~ 74°C	-37°~ 74°C	0 to 50°C
Installation Method	Panel Mountable	Panel/Rack Mountable	Panel Mountable	Panel/Rack Mountable	Panel Mountable
Supported Device Drivers					
Windows 2000/Server 2003/XP	Yes	Yes	Yes	Yes	Yes
Windows Server 2008	Yes	Yes	Yes	Yes	Yes
Windows Vista	Yes	Yes	Yes	Yes	Yes
Windows 7	Yes	Yes	Yes	Yes	Yes
Linux	Yes	Yes	Yes	Yes	No
Software					
TCP, UDP Socket	Yes	Yes	Yes	Yes	Yes
PortVision® Plus remote monitoring & management	Yes	Yes	Yes	Yes	Yes
Web-based configuration	Yes	Yes	Yes	Yes	Yes
SSL & SSH encryption	Yes	Yes	Yes	Yes	Yes
E-mail event notification	Yes	Yes	Yes	Yes	Yes
Certifications					
RoHS 2002/95/EC	Yes	Yes	Yes	Yes	Yes
CE/FCC/UL/RoHS	Yes	Yes	Yes	Yes	Yes
NEMA TS2	Yes	Yes	Yes	Yes	No
Warranty	5 Years	5 Years	5 Years	5 Years	5 Years