



# SFP Single-Mode 100BASE-FX 100KM Fast Ethernet (Extended Temp)

Part Number: 1200069

Control offers SFP transceivers in a variety of models. If you have questions concerning the best SFP transceiver for a particular application, please contact your Control sales or technical support representative.



## SPECIFICATIONS

### HARDWARE

**Bus Interface Specification**  
100BASE-FX

**Dimensions** 2.2" x 0.53" x 0.5"  
55.9 x 13.5 x 12.7 cm

**Hot Pluggable** Yes

**Product Weight** 0.6 oz  
0.017 kg

### ENVIRONMENTAL SPECIFICATIONS

**Air temperature**  
System On -40° to 85° C  
System Off -40° to 85° C

**Operating Humidity**  
(non-condensing) 0% to 85%

### OPTICAL FIBER SPECIFICATION

**Fiber Mode** Single-Mode  
**Link Distance (Max)** 100KM  
**Connector Type** (1) Duplex LC  
**Fiber Cable Type** 9/125um

**Data rate** 125Mbps  
**Wavelength** 1550nm  
**Transmit Power (Min)** -5 dBm  
**Transmit Power (Max)** 0 dBm  
**Receive Sensitivity (Min)** 35 dBm  
**Receive Sensitivity (Max)** 0 dBm  
**Link Budget** 30 dBm  
**Supported Communication Standard**  
100BASE-FX Full-Duplex or Half-Duplex  
IEEE802.3 100BASE-FX  
SFP Multi-Source (MSA) Compliant

### EXPORT INFORMATION

**Packaged Shipping Weight** 1.5 oz  
0.27 kg  
**Package Dimensions** 4.5" x 2.50" x 1.0"  
114.3 x 63.5 x 25.4 mm  
**Country of Origin** USA  
**ECCN** 5A991  
**Schedule B Number** 8517.62.0050

**connect. communicate. control.**

**Warranty Information**  
Control offers a 30-day satisfaction guarantee and 5-year limited warranty.

**Sales Support**  
+1.763.957.6000  
sales@comtrol.com

**Technical Support**  
+1.763.957.6000  
www.comtrol.com/support

**Email, FTP, and Web Support**  
info@comtrol.com  
ftp.comtrol.com  
www.comtrol.com