

# SFPs

## SMALL FORM-FACTOR PLUGGABLES PRODUCT COMPARISON CHART

Part Number	Description	Mode	Distance	Temperature	Wavelength
<b>Gigabit SFPs</b>					
<a href="#">1200044</a>	1000Mbps-SX Fiber Transceiver	Multi	550M	-10 to 70°C	850nm
<a href="#">1200059</a>	1000Mbps-SX Fiber Transceiver	Multi	550M	-40 to 85°C	850nm
<a href="#">1200088</a>	1000Mbps-MLX Fiber Transceiver	Multi	2KM	-40 to 85°C	1310nm
<a href="#">1200045</a>	1000Mbps-LX Fiber Transceiver	Single	10KM	-10 to 70°C	1310nm
<a href="#">1200060</a>	1000Mbps-LX Fiber Transceiver	Single	10KM	-40 to 85°C	1310nm
<a href="#">1200066</a>	1000Mbps-LH Fiber Transceiver	Single	20KM	-40 to 85°C	1310nm
<a href="#">1200061</a>	1000Mbps-LH Fiber Transceiver	Single	30KM	-40 to 85°C	1310nm
<a href="#">1200067</a>	1000Mbps-LHX Fiber Transceiver	Single	40KM	-40 to 85°C	1310nm
<a href="#">1200094</a>	1000Mbps-XD Fiber Transceiver	Single	50KM	-40 to 85°C	1550nm
<a href="#">1200065</a>	1000Mbps-ZX Fiber Transceiver	Single	70KM	-40 to 85°C	1550nm
<a href="#">1200095</a>	1000Mbps-ZX Fiber Transceiver	Single	90KM	-40 to 85°C	1550nm
<a href="#">1200068</a>	1000Mbps-LHX Fiber Transceiver	Single	110KM	-40 to 85°C	1550nm
<b>Fast Ethernet BIDI SFPs</b>					
<a href="#">1200076</a>	100Mbps BIDI 1310nm Fiber Transceiver	Single	20KM	-40 to 85°C	TX-1310nm RX-1550nm
<a href="#">1200077</a>	100Mbps BIDI 1550nm Fiber Transceiver	Single	20KM	-40 to 85°C	TX-1550nm RX-1310nm



Part Number	Description	Mode	Distance	Temperature	Wavelength
<b>100 Mbit SFPs</b>					
<a href="#">1200042</a>	100Mbps Fiber Transceiver	Multi	2KM	-10 to 70°C	1310nm
<a href="#">1200057</a>	100Mbps Fiber Transceiver	Multi	2KM	-40 to 85°C	1310nm
<a href="#">1200092</a>	100Mbps Fiber Transceiver	Single	20KM	-40 to 85°C	1550nm
<a href="#">1200043</a>	100Mbps Fiber Transceiver	Single	30KM	-10 to 70°C	1310nm
<a href="#">1200058</a>	100Mbps Fiber Transceiver	Single	30KM	-40 to 85°C	1310nm
<a href="#">1200086</a>	100Mbps Fiber Transceiver	Single	60KM	-40 to 85°C	1310nm
<a href="#">1200069</a>	100Mbps Fiber Transceiver	Single	100KM	-40 to 85°C	1550nm
<a href="#">1200093</a>	100Mbps Fiber Transceiver	Single	120KM	-40 to 85°C	1310nm
<b>Gigabit BIDI SFPs</b>					
<a href="#">1200080</a>	1000Mbps BIDI Fiber Transceiver	Single	10KM	-40 to 85°C	1310nm
<a href="#">1200081</a>	1000Mbps BIDI Fiber Transceiver	Single	10KM	-40 to 85°C	1550nm
<a href="#">1200082</a>	1000Mbps BIDI Fiber Transceiver	Single	20KM	-40 to 85°C	1310nm
<a href="#">1200083</a>	1000Mbps BIDI Fiber Transceiver	Single	20KM	-40 to 85°C	1550nm

Control offers a comprehensive line of SFPs to support our RocketLinx industrial Ethernet switches.