



SFP Single-Mode 70KM 1000BASE-ZX (Extended Temperature)

Part Number: 1200065

Control offers SFP transceivers in a variety of models. If you have questions concerning the best SFP transceiver for a particular application, please contact your Control sales or technical support representative.



SPECIFICATIONS

HARDWARE

Bus Interface Specification	Gigabit Ethernet Fiber 1000BASE-ZX
Dimensions	2.2" x 0.53" x 0.5"
	55.9 x 13.5 x 12.7 cm
Hot Pluggable	Yes
Product Weight	0.6 oz
	0.017 kg

ENVIRONMENTAL SPECIFICATIONS

Air temperature	
System On	-40° to 85° C
System Off	-40° to 85° C
Operating Humidity	
(non-condensing)	0% to 85%

OPTICAL FIBER SPECIFICATION

Fiber Mode	Single-Mode
Link Distance (Max)	70KM
Connector Type	(1) Duplex LC
Fiber Cable Type	9/125um
Data rate	1.25 Gbps

Wavelength	1550nm
Transmit Power (Min)	0 dBm
Transmit Power (Max)	5 dBm
Receive Sensitivity (Min)	-27 dBm
Receive Sensitivity (Max)	-3 dBm
Link Budget	27 dBm
Supported Communication Standard	1000BASE-ZX Full-Duplex or Half-Duplex
	IEEE802.3z Gigabit Ethernet standard
	SFP Multi-Source (MSA) Compliant

EXPORT INFORMATION

Packaged Shipping Weight	1.5 oz
	0.27 kg
Package Dimensions	4.5" x 2.50" x 1.0"
	114.3 x 63.5 x 25.4 cm
Country of Origin	USA
ECCN	5A991
Schedule B Number	8517.62.0050

connect. communicate. control.

Warranty Information
Control offers a 30-day satisfaction guarantee and 5-year limited warranty.

Sales Support
+1.763.957.6000
sales@comtrol.com

Technical Support
+1.763.957.6000
www.comtrol.com/support

Email, FTP, and Web Support
info@comtrol.com
ftp.comtrol.com
www.comtrol.com