



DeviceMaster® FreeWire

Part Number: 31300-7



KEY FEATURES AND BENEFITS

- Industry's most advanced wireless security, supporting WPA, WPA2, WEP and PSK or 802.11x authentication with TTLS, TLS, LEAP, PEAP, and FAST
- 802.11 b/g wireless communications with option of direct 10/100 Ethernet connection
- Enterprise level security features including access control lists, protocol and application enable/disable control, read and write configuration passwords, and SNMP community name configuration
- Widest variety of management options, including HTTP, Telnet, Windows-based utility, console port, and SNMP
- Rugged, IP40 rated steel housing with side flange mounting supports a wide variety of installation options
- Windows COM port redirector software ensures seamless integration with applications by mapping remote serial ports to local PC COM ports
- IPv6 support
- RoHS2 compliant under CE

PRODUCT DESCRIPTION

DeviceMaster FreeWire leverages the industry's most advanced security to enable communication to remote serial devices via 802.11b/g wireless or direct wired 10/100 Ethernet technologies. The latest addition to Control's DeviceMaster family of serial device servers, FreeWire is ideal for situations where LANs are not feasible, where wiring is difficult or where devices are moved periodically. FreeWire's flexible connection options provide the ultimate freedom of choice.

Like other DeviceMaster products, FreeWire is packaged in a rugged, galvanized, IP40-rated steel enclosure, facilitating installation in a wide variety of environments. And FreeWire is

fast and easy to install and manage: It includes an extensive management application that allows users to set up, configure, manage and maintain multiple device servers quickly and simultaneously. FreeWire also includes COM port redirector software for mapping local COM ports to the remote FreeWire serial connection and an integrated web server for remote configuration from any networked PC, Telnet and serial console administration.

All of this from Control, one of the oldest, most respected manufacturers of device connectivity servers in the industry.



DEVICEMASTER SPECIFICATIONS

HARDWARE

Bus Interface Specification

Enclosure

Metal IP40 Rating

Installation Method

Panel Mounting

LED Indicators

Power, 10Mbps, 100Mbps

Dimensions

4.95" x 0.95" x 2.96"

125.7 x 24.1 x 75.2 mm

Product Weight

.76 lbs

0.34 kg

ELECTRICAL SPECIFICATIONS

Device

DC Input Voltage 4.75 - 5.25 VDC

Current Consumption

+5VDC 600 mA

Power Consumption (max) 3 W

Control External Power Supply

Output Voltage 5VDC

Output Current +5VDC 2.5 A

Line Frequency 50/60 Hz

Line Voltage 100-240 VAC

ESD Surge Protection

Provides minimum of 15KV protection for all serial lines

ENVIRONMENTAL SPECIFICATIONS

Air Temperature

System on 0° to 50° C

System off -20° to 70° C

Operating Humidity

Non-condensing 10% to 90%

Altitude

0 to 10,000 Feet

0 to 3,048 m

Heat Output

10.24 BTU/Hr

SERIAL COMMUNICATIONS

Connector Type

DB9 Male

Supported Standards

RS-232

Baud Rates

300 bps to 921 kbps

Receive Buffer

1,024 Bytes

Transmit Buffer

4,096 Bytes

Device Driver Data Control

Data Bits 7 or 8

Parity Odd, even or none

Stop Bits 1 or 2

Flow Control

Hardware or software

NETWORK SPECIFICATIONS

Ethernet Interface 10/100 BASE-T

WLAN/Ethernet Protocols

802.11g, ARP, TCP, Telnet, ICMP, SNMP, DHCP, BOOTP,

Auto

IP, HTTP, SMTP, TFTP, SLP, DNS, Dynamic DNS, RFC2217,

WLAN

roaming

Wireless Security

WPA and WPA2 (personal and enterprise modes), PAP,

MS-

CHAPv2, 802.1x EAP with TLS/TTLS/LEAP/PEAP/FAST,

WEP

Data rates with automatic fallback

54MBPS, 48MBPS, 36MBPS, 24MBPS, 18MBPS, 12MBPS,

11MBPS, 9MBPS, 6MBPS, 5.5MBPS, 2MBPS, or 1MBPS

Frequency Range 2.4 GHZ ISM Band

Operating Range 100 m

Transmitter Output

802.11g mode

Channel 2-10, 12, 13 15 dBm

Channel 11 14 dBm

Channel 1 12 dBm

802.11b mode

Channel 14 14 dBm

Receiver Sensitivity (PER <10%)

11g:

54Mbps -68 dB Min

48Mbps -68 dB Min

36Mbps -75 dB Min

24Mbps -79 dB Min

18Mbps -82 dB Min

12Mbps -84 dB Min

9Mbps -87 dB Min

6Mbps -88 dB Min

11b:

11Mbps -82 dB Min

5.5Mbps -84 dB Min

2Mbps -86 dB Min

1Mbps -88 dB Min

External Antenna Type

Detachable RP-SMA connector with dipole swivel

2.0dB gain

Operating Mode

Infrastructure, ad-hoc

REGULATORY STANDARDS

Emissions

European Standard EN55022

EN 301 489-1

EN 301 489-17

EN 300 328

FCC Part 15 Subpart B and Subpart C: Class B limit AS/

NZS 4268

CISPR 22 Class B limit

Immunity

EN55024:

IEC 1000-4-2/EN61000-4-2: ESD

IEC 1000-4-3/EN61000-4-3: RF

IEC 1000-4-4/EN61000-4-4: Fast Transient

IEC 1000-4-5/EN61000-4-5: Surge

IEC 1000-4-6/EN61000-4-6: Conducted Disturbance

IEC 1000-4-11/EN61000-4-11: Dips and Voltage

Variations

Safety

IEC 60950/EN60950

CSA C22.2 No. 60950/UL 60950 Third Edition

Other

RoHS2 compliant under CE

MANAGEMENT AND UTILITIES

Serial Port Emulator Software

Management Utility

Web Browser Interface

Console Accessible Via Serial Port or TELNET

Simple Network Management Protocol (SNMP)

MB I and II; IP

Firmware Downloads Via TCP/IP (master mode

tftp, slave mode TFTP, or BOOTP)

On-line HELP

EXPORT INFORMATION

Packaged Shipping Weight

2.13 lbs

0.97 kg

Packaged Dimensions

10.25" x 7.5" x 3.38"

260.4 x 190.5 x 85.9 mm

Country of Origin

Japan

ECCN

5A992

Schedule B Number

8473.30.1180

FCC License Number

N6C-5X10WG

FEATURES

SNMP Support

RoHS2 Compliant

2-Year Warranty

REGULATORY APPROVALS



Warranty Information

Control offers a 30-day satisfaction guarantee and 5-year limited warranty.

Sales Support

+1.763.957.6000
sales@comtrol.com

Technical Support

+1.763.957.6000
www.comtrol.com/support

Email, FTP, and Web Support

info@comtrol.com
ftp.comtrol.com
www.comtrol.com