



## MeanWell SDR-480-48

Part Number: 32124-8



### KEY FEATURES AND BENEFITS

- Output adjustable from 48-55VDC
- Rated power 480 watts
- High efficiency 94% and low power dissipation
- 150% peak load capability
- Built-in active PFC function, PF>0.94
- Protections: short circuit / overload / over voltage / over temperature
- Cooling by free air convection
- Built-in constant current limiting circuit
- Can be installed on DIN rail TS-35/7.5 or 15
- UL 508(industrial control equipment) approved
- EN61000-6-2(EN50082-2) industrial immunity level
- Built-in DC OK relay contact
- 100% full load burn-in test

### PRODUCT DESCRIPTION

The Mean Well SDR-480-48 is an industrial DIN rail power supply with 94% efficiency and built-in protections against short circuits, overloads, over voltage and over temperature.

This power supply is ideal for PoE and PoE Plus applications because it provides 48 volts and 480

watts to power multiple high-power devices. With UL 508 (industrial control equipment) approval and a wide operating temperature range the SDR-480-48 is reliable in even the most demanding environments.

# SPECIFICATIONS

## HARDWARE

### Enclosure

UL Compliant Fully Isolated Plastic Housing

### Installation Method

DIN RAIL (35MM)

### DIN Rail Spec

TS35/7.5 or TS35/15

### LED Indicators

Output Voltage Status

### Dimensions

4.9" x 3.4" x 5.1"

### Product Weight

3.4 lb

## INPUT SPECIFICATIONS

### Connector Type

Screw Terminals

### AC Voltage Range

90 - 264VAC

### Frequency Range

47 - 63Hz

### Power Factor (PF Typ.)

≥ 0.94 / 230VAC

≥ 0.99 / 115VAC

### DC Voltage Range

127 - 370VDC

### Efficiency (Typ.)

94%

### AC Current (Typ.)

5A / 115VAC

2.5A / 230VAC

### Inrush Current (Typ.)

40A / 115VAC at Cold Start

80A / 230VAC at Cold Start

### Leakage Current

< 0.8mA / 240VAC

## OUTPUT SPECIFICATIONS

### Connector Type

Screw Terminals

### DC Voltage

48VDC

### Rated Current

10A

### Current Range

0 - 10A

### Rated Power

480W

### Voltage Adjustable Range

48 - 55VDC

### Voltage Tolerance

±1%

### Ripple and Noise (Max.)

120mVp-p

### Output Load Derating

80% of full load at 70°C

### Line Regulation

±0.5%

### Load Regulation

±1%

### Set-Up, Rise Time

1500ms, 150ms/230VAC

3000ms, 150ms/ 115VAC at Full Load

### Hold Up Time (Typ.)

14ms / 230VAC at Full Load

### DC OK Relay Contact Rating

60VDC/0.3A

30VDC/1A

30VAC/0.5A resistive load

## PROTECTION SPECIFICATIONS

### Short Circuit/ Overload

Overload Power

110 ~ 150% of rated output power for 3 sec.

Overload Protection Type

Constant Current Limiting Recovers automatically after fault condition is removed

### Over Voltage

Rated Voltage

56 - 65VDC

Over Voltage Protection Type

Shutdown output voltage with auto-recovery

### Over Temperature

Rated Temperature

105°C ± 5°C detection on power transistor heat sink

Over Temperature Protection Type

Shutdown output voltage, recover automatically after temperature drops

## ENVIRONMENTAL SPECIFICATIONS

### Air temperature

System On

-25 to 70°C

System Off

-40 to 85°C

### Operating Humidity (non-condensing)

20% to 95%

### Vibration

Component: 10 ~ 500Hz, 2G 10min./1cycle, period for

60min. each along X, Y, Z axes ;

Mounting: IEC60068-2-6 compliant

### Mean time between failures

12.9 years

## EXPORT INFORMATION

### Packaged Shipping Weight

3.5 lb

### Package Dimensions

6.8" x 4.8" x 6.0"

### UPC Code

7-56727-32124-8

### ECCN

4A994

### Schedule B Number

8504.40.6007

### Warranty

3 Years

## REGULATORY APPROVALS

### Emissions

European Standard EN61204-3

European Standard EN55022

Class B Limit

IEC 1000-3-2/EN61000-3-2: Harmonic

Class A Limit

IEC 1000-3-2/EN61000-3-2: Flicker

### Immunity

European Standard EN61204-3

European Standard EN55024:

IEC 1000-4-2/EN61000-4-2: Electrostatic Discharge (ESD)

IEC 1000-4-3/EN61000-4-3: Radiated Radio-Frequency (RF)

IEC 1000-4-4/EN61000-4-4: Fast Transient/Burst

IEC 1000-4-5/EN61000-4-5: Surge

IEC 1000-4-6/EN61000-4-6: Conducted Disturbance

IEC 1000-4-8/EN61000-4-8: Magnetic field

IEC 1000-4-11/EN61000-4-11: Dips and Voltage Variations

### Safety

UL60950, UL508

### Other

European Standard: RoHS 2 compliant under CE

### Regulatory Approvals



### Warranty Information

Control offers a 30-day satisfaction guarantee and 3-year limited warranty.

### Sales Support

+1.763.957.6000  
sales@comtrol.com

### Technical Support

+1.763.957.6000  
www.comtrol.com/support

### Email, FTP, and Web Support

info@comtrol.com  
ftp.comtrol.com  
www.comtrol.com