

ROCKETPORT

SERIAL HUB PRODUCT COMPARISON CHART



RocketPort Serial Hub	USB Serial Hub II 4-Port (98295-1)	USB Serial Hub III 8-Port (98296-8)
HARDWARE		
Serial Ports	4	8
Serial Baud Rate	300bps-230.4Kbps	300bps-230.4Kbps
Serial Interface	RS232	RS232
Power Consumption	1.7W	2.5W
Serial Surge Protect	4KV	4KV
Dimension	7.5" x 8.75" x 3.0"	7.825" x 1.625" x 3.625"
ENVIRONMENTAL		
MTBF	30.7 Years	17.1 Years
Enclosure	Black Plastic	Black Plastic
Operating Temperature	0-50°C	0-50°C
SERIAL COMMUNICATIONS		
Data Bits	7 or 8	7 or 8
Parity	odd, even or none	odd, even or none
Stop Bits	1 or 2	1 or 2
Flow Control	Hardware or Software	Hardware or Software
DEVICE DRIVERS		
Linux	Yes	Yes
Windows Server 2003/2008	Yes	Yes
Windows VISTA/XP/7/2000	Yes	Yes
CERTIFICATIONS		
CE/FCC/UL/RoHS2	CE/FCC/UL/RoHS2	CE/FCC/UL/RoHS2
Warranty	5 Years	5 Years